


## Sealing screw Series C-VSTI-R-ED



|                       |                                                                 |
|-----------------------|-----------------------------------------------------------------|
| Design type           | Sealing screw                                                   |
| Male thread           | 1/8...1 1/2" BSP, with elastic seal                             |
| Material              | Steel galvanized                                                |
| according to standard | EN ISO 8434-1 (DIN 2353)                                        |
| Seal                  | NBR (FKM on request)                                            |
| Medium                | neutral liquids and gases that do not attack the materials used |
| Medium temperature    | -35...+100°C                                                    |
| Operating pressure    | Nominal pressure according to table                             |

### Dimensions



| Series | PN [bar] | G     | D1 | L1   | L2 | CH1 | Type           |
|--------|----------|-------|----|------|----|-----|----------------|
| S      | 400      | 1/8   | 14 | 12   | 8  | 5   | C-VSTIR1/8ED   |
|        |          | 1/4   | 19 | 17   | 12 | 6   | C-VSTIR1/4ED   |
|        |          | 3/8   | 22 | 17   | 12 | 8   | C-VSTIR3/8ED   |
|        |          | 1/2   | 27 | 19   | 14 | 10  | C-VSTIR1/2ED   |
|        |          | 3/4   | 32 | 21   | 16 | 12  | C-VSTIR3/4ED   |
|        |          | 1     | 40 | 22,5 | 16 | 17  | C-VSTIR1ED     |
|        | 250      | 1 1/4 | 50 | 22,5 | 16 | 22  | C-VSTIR1 1/4ED |
|        |          | 1 1/2 | 55 | 22,5 | 16 | 24  | C-VSTIR1 1/2ED |

Illustrations non-binding

Design, dimensional and material changes reserved

Pneumatics / Fittings and couplings / Tube fittings / Tube fittings - Zinc plated steel ISO 8434-1 (DIN 2353) / Plug screw Series C-VSTI-R-ED

