

Ugao Pregradna spojnica Serija A-WSV-71



Osnovno telo sa maticom i sečnim prstenom



B4-Rezni prsten






B3-Rezni prsten

Konstrukcija	Priključak sa sečnim prstenom, sa B3 ili B4 prstenom za sečenje
Spoljašnji prečnik cevi	6...42mm
Materijal	Nerđajući čelik 1.4571
Odgovarajuće standard	EN ISO 8434-1 (DIN 2353)
Medij	neutralne tečnosti i gasovi, koji ne napadaju upotrebljene materijale
Temperatura medijuma	B3-Rezni prsten -60...+200°C B4-Rezni prsten FKM -25...+200°C
Radni pritisak	Nazivni pritisak prema tabeli do 50°C, preko 50°C 4,5% Redukcija pritiska, preko 100°C 11% Redukcija pritiska



Dimenzije



Osnovno telo

sa B4-rezni prsten

sa B3-rezni prsten

* = Opseg stezanja do 16mm

Serija	PN [bar]	Prečnik cevi	m	L1	L2	L3	L4	L5	L6	L7	D1	CH1	CH2	CH3	Tip Osnovno telo	Tip sa B4- prstenom	Tip sa B3- prstenom
L	315	6	12x1,5	19	12	34	14	27	19	42	17	12	17	14	A-WSV06LX	A-WSV06ZL	A-WSV06L
		8	14x1,5	21	14	34	17	27	21	42	19	12	19	17	A-WSV08LX	A-WSV08ZL	A-WSV08L
		10	16x1,5	22	15	35	18	28	22	43	22	14	22	19	A-WSV10LX	A-WSV10ZL	A-WSV10L
		12	18x1,5	24	17	36	20	29	24	44	24	17	24	22	A-WSV12LX	A-WSV12ZL	A-WSV12L
		15	22x1,5	28	21	38	23	31	28	46	27	19	30	27	A-WSV15LX	A-WSV15ZL	A-WSV15L
		18	26x1,5	31	23,5	40	24	32,5	31	49	32	24	36	32	A-WSV18LX	A-WSV18ZL	A-WSV18L
	160	22	30x2	35	27,5	42	30	34,5	35	51	36	27	41	36	A-WSV22LX	A-WSV22ZL	A-WSV22L
		28	36x2	38	30,5	43	34	35,5	38	52	42	36	46	41	A-WSV28LX	A-WSV28ZL	A-WSV28L
		35	45x2	45	34,5	47	39	36,5	45	58	50	41	55	50	A-WSV35LX	A-WSV35ZL	A-WSV35L
		42	52x2	51	40	47	43	36	51	59	60	50	65	60	A-WSV42LX	A-WSV42ZL	A-WSV42L
S	630	6	14x1,5	23	16	36	17	29	23	44	19	12	19	17	A-WSV06SX	A-WSV06ZS	A-WSV06S
		8	16x1,5	24	17	36	18	29	24	44	22	14	22	19	A-WSV08SX	A-WSV08ZS	A-WSV08S
		10	18x1,5	25	17,5	37	20	29,5	25	46	24	17	24	22	A-WSV10SX	A-WSV10ZS	A-WSV10S
		12	20x1,5	29	21,5	38	21	30,5	29	47	27	17	27	24	A-WSV12SX	A-WSV12ZS	A-WSV12S
		14	22x1,5	30	22	40	23	32	30	50	30	19	30	27	A-WSV14SX	A-WSV14ZS	A-WSV14S
	400	16	24x1,5	33	24,5	40	24	31,5	33	50	32	24	32	30	A-WSV16SX	A-WSV16ZS	A-WSV16S
		20	30x2	37	26,5	44	30	33,5	37	55	41	27	41	36	A-WSV20SX	A-WSV20ZS	A-WSV20S
		25	36x2	42	30	47	34	35	42	59	46	36	46	46	A-WSV25SX	A-WSV25ZS	A-WSV25S
		30	42x2	49	35,5	51	39	37,5	49	64	50	41	50	50	A-WSV30SX	A-WSV30ZS	A-WSV30S
	315	38	52x2	57	41	53	43	37	57	68	65	50	65	60	A-WSV38SX	A-WSV38ZS	A-WSV38S

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materialne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Priključci sa usečnim prstenom / priključak sa usečnim prstenom - nerđajući čelik AISI 316 Ti ISO 8434-1 (DIN 2353) / kolenasti pregradni priključak serije A-WSV-71

Verzija 9

138516 / Generisano 2026/38 SR

PROIZVEDENO U EVROPI

 **+381 11 2399521**

+381 11 23993
balkan@stasto.eu

© STASTO Automatizacija d.o.o.

www.stasto.rs

Otvori seriju online

Strana 2 / 2

