
Partnership. With Guarantee.

# Solenoid coil
# Series BDA



| | |
|---|---|
| Sheathing | Thermoplastic |
| Electrical connection | connector according to EN175301-803 Form A, Connector width 32mm (see separate data sheet) |
| Standard voltage | 12VDC, 24VDC, 230V/50-60Hz, 24V/50-60Hz |
| Special voltages | 42V/50Hz, 48V/50Hz, 110V/50-60Hz, 380V/50-60Hz, further on request |
| Permissible voltage fluctuation | DC -5/+10%, AC -15/+10% |
| Duty cycle | 100% (Continuous operation) |
| Ambient temperature | -10...+40°C |
| Insulation class | F |
| Degree of protection | IP65 according to EN 60529 with correctly mounted device connector (Protection against dust ingress and water jets) |

## Technical data




| Voltage | Power consumption at 20°C | Type |
|---|---|---|
| 12VDC | 8W | BDA08012CS |
| 24VDC | 8W | BDA08024CS |
| 24V/50-60Hz | 14,5VA | BDA08024DS |
| 42V/50Hz | 14,5VA | BDA08042AS |
| 48V/50Hz | 14,5VA | BDA08048AS |
| 110VDC | 8W | BDA08110CS |
| 110V/50-60Hz | 14,5VA | BDA08110DS |
| 220-230V/50-60Hz | 14,5VA | BDA08223DS |
| 380V/50-60Hz | 14,5VA | BDA08380DS |
| | | |

Illustrations non-binding
Design, dimensional and material changes reserved



Version 11
140187 / Generated 2026/44 EN
MADE IN EUROPE

+43 512 52076
austria@stasto.eu
© STASTO Automation KG