Partnership. With Guarantee.

Double nipple
Series A-3105

Connection	1/8"...1"BSP
Material	Stainless steel 1.4571
Medium	Compressed air, neutral gases, Liquids that do not chemically attack the materials
Medium temperature	-60°C...+200°C
Operating pressure	Nominal pressure according to table

Dimensions



PN [bar]	A	B	L1	L2	L3	CH1	Type
400	G1/8"	G1/8"	25	8	8	14	A-310501
400	G1/8"	G1/4"	30	8	11	17	A-310502
400	G1/4"	G1/4"	34	11	11	19	A-310504
400	G1/4"	G3/8"	33	11	12	22	A-310505
400	G1/4"	G1/2"	39	11	14	27	A-310506
400	G3/8"	G3/8"	34	12	12	22	A-310508
400	G3/8"	G1/2"	41	12	14	27	A-310509
400	G3/8"	G3/4"	44	12	16	32	A-310510
400	G1/2"	G1/2"	44	14	14	27	A-310511
400	G1/2"	G5/8"	44	14	16	30	A-310512
400	G1/2"	G3/4"	45	14	16	32	A-310513
400	G1/2"	G1"	51	14	19	41	A-310514
400	G3/4"	G5/8"	47	16	16	32	A-310517
400	G3/4"	G3/4"	46	16	16	32	A-310518
400	G3/4"	G1"	51	16	19	41	A-310519
400	G1"	G1"	55	19	19	41	A-310522

Illustrations non-binding
Design, dimensional and material changes reserved

Version 7
190228 / Generated 2026/39 EN
MADE IN EUROPE

+43 512 52076
austria@stasto.eu
© STASTO Automation KG